

BACK BAR REFRIGERATOR: TBB-3SG



≡ **FEATURES / BENEFITS** ≡

■ **EFFICIENT REFRIGERATION SYSTEM**

Turbo Air's refrigerators are designed with oversized and balanced refrigeration systems. These include efficient evaporators and condensers for faster cooling and greater efficiency.

■ **FORCED AIR COOLING SYSTEM**

Fast cooling and balanced temperature throughout the cabinet.

■ **STAINLESS STEEL COUNTERTOP AND INTERIOR**

The exterior of cabinet is constructed with heavy gauge reinforced stainless steel countertop and wear-resistant black vinyl coated galvanized steel. Interior is stainless steel floor and door liners with white painted galvanized steel inside walls. Turbo Air Back Bar model guarantees utmost in cleanliness and long product life. It also can add a touch of style to the most refined setting.

■ **LED INTERIOR LIGHTING FOR ALL MODELS**

Bright LED interior lighting is specifically designed for perfect visibility throughout the interior.

■ **HIGH-DENSITY POLYURETHANE INSULATION**

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

■ **ADJUSTABLE, HEAVY DUTY, PE (POLYETHYLENE) COATED WIRE SHELVES**

■ **ERGONOMICALLY DESIGNED DOORS**

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ **SIDE MOUNT COMPRESSOR UNIT**

By positioning the compressor on the side of the unit, refrigerators can now be serviced without being moved.

Model	Swing Door	Capacity (litres)	#of Shelves	HP	AMPS	Crated Weight (kg)	W x D x H (mm)
<b>TBB-3SG</b>	<b>2</b>		<b>4</b>	<b>1/4</b>	<b>2.0</b>	<b>140</b>	<b>1492x692x1065</b>

Ver.DEC.2015

BACK BAR REFRIGERATOR: TBB-3SG

1	Classification	Refrigerator
2	Cabinet Dimensions(mm)	1754 x 692 x 942
3	Capacity(Liters)	651
4	Inner Temperature(Celsius)	0 ~ 8
5	Doors	2
6	# of Shelves	6
7	Refrigerant	R-134a
8	Compressor(HP)	TBB-3SG 1/3, TBB-3SB 1/4
9	Cooling Type	Fan Cooling Type
10	Control Type	Analog
11	Insulation Type	Polyurethane Cyclopentane + CFC Free
12	Amps(A)	
13	Voltage(V/Hz/Ph)	220-240/50/1
14	Power(W)	
15	Weight(Kg)	TBB-3SG 160, TBB-3SB 135

